

F θ lens

For YAG laser

F θ lens is used when a galvano mirror or polygon mirror is used to scan a laser beam in two dimensions.

The lens distortion characteristic is used to scan the focused spot of the beam scanned by the mirror's constant velocity rotational motion at a uniform speed on the focal plane.

Features

- ◎ For fundamental wave (**1064nm**) and harmonics (**266nm, 355nm, 532nm**) of YAG laser
- ◎ **Good focus spot characteristics** with minimal aberration
- ◎ **Interchangeable window** protects the lens from scattered objects generated from the workpiece

Able to customize other wavelengths, multiple wavelengths, long working distances, wide scan areas, etc.

Use

- ◎ High-speed drilling of printed wiring boards
- ◎ High-speed marking of electronic components
- ◎ High-speed marking of resin parts
- ◎ Laser processing
- ◎ Laser drilling
- ◎ Laser welding of synthetic materials
- ◎ Laser cutting



Optical components, optical systems, lasers



KYOCERA SOC Corporation

Contact us:

TEL: +81-45-931-6592

URL: <https://www.ksoc.co.jp/en/shiryo/>

Responsible for sales: Kobayashi and Kimura




For YAG laser

F θ lens

● Specification

Model	FT250/4-1064	FT150/4-1064	FT150/2-532S	FT150/2-355	FT100/2-355T	FT150/2-266S	
Wavelength	1064nm	1064nm	532nm	355nm	355nm	266nm	
Focal length	250mm	150mm	150mm	150mm	101mm	150mm	
Scanning range	ϕ 140mm	ϕ 140mm	ϕ 72mm	ϕ 72mm	ϕ 56mm	ϕ 72mm	
Incident beam dia.	ϕ 12mm	ϕ 12mm	ϕ 12mm	ϕ 12mm	ϕ 10mm	ϕ 12mm	
Focus spot dia. (1/e ²)	ϕ 40 μ m	ϕ 24 μ m	ϕ 12 μ m	ϕ 8 μ m	ϕ 7 μ m	ϕ 6 μ m	
f θ distortion(Max)	0.10%	0.10%	0.04%	0.02%	0.02%	0.04%	
Transmittance	96%	96%	94%	92%	90%	90%	
Telecentric	—	—	—	—	○	—	
Window model No.	C60-1064	C90-1064	C56-532	C62-355	C81-355	C66-266	
Size(mm)	WD	301	174.7	168	147	108	145.9
	F.B.f	315.6	199	209.5	212	170.3	209.4
	a	20	20	25	25	20	25
	b	15	12.8	19.5	16	13	16
	c	8.5	5.2	3.5	7	10	7
	d	6	6	6	6	6	6
	e	6	6	6	6	6	6
	f	17.5	24.3	31.5	65	67.3	63.5
	g	35	35	35	35	35	35
	h	53	64	48	48	54	58
	i	M60xP1.0	M90xP1.0	M60xP1.0	M60xP1.0	M90xP1.0	M60xP1.0
	j	ϕ 62	ϕ 92	ϕ 62	ϕ 62	ϕ 92	ϕ 62
	k	ϕ 68	ϕ 100	ϕ 70	ϕ 80	ϕ 100	ϕ 78

● Dimensions



The contents of this document are subject to change without notice. Contact us for further information.

Optical components, optical systems, lasers



KYOCERA SOC Corporation

Contact us:

TEL: +81-45-931-6592

URL: <https://www.ksoc.co.jp/en/shiryo/>

Responsible for sales: Kobayashi and Kimura

